## **Declaration of performance** No. 5001 - v2

Unique identification code of the product-type:	LIP 2K Vådrumssystem Watertight covering kit
Intended uses:	Liquid applied watertight covering kit for wet room floors and walls
Manufacturer:	LIP Bygningsartikler A/S, Industrivej 16, 5580 Nørre Aaby, Denmark
System/s of AVCP:	2+
European Assessment Document:	Guideline for European Technical Approval (ETAG) No. 022 Watertight covering kits for wet room floor and/or walls, Part 1 Liquid applied coverings with or without wearing surface, edition April 2007, used as European Assessment Document (AED)
European Technical Assessment:	ETA-14/0003 of 2023/09/11
Technical Assessment Body	ETA-Danmark A/S
Notified body:	1073
Declared performance	
Reaction to fire	NPD
Release of dangerous substances	No dangerous materials
Vapour permeability	RH 100 $\Rightarrow$ 75 %: Z <sub>p</sub> = 218 GPa $\cdot$ s $\cdot$ m <sup>2</sup> /kg and equivalent
	s <sub>d</sub> = 42.5 m
	RH 94 $\rightarrow$ 50 %: Z <sub>p</sub> = 236 GPa $\cdot$ s $\cdot$ m <sup>2</sup> /kg and equivalent
	s <sub>d</sub> = 46.1 m
Water tightness	Pass
Crack bridging ability	Category 1
Bond strength	Category 2 (≥ 0.5 MPa)
Scratching resistance	NPD
Joint bridging ability	Category 2
Water tightness around penetrations	Category 2
Resistance to temperature	Category 2 (≥ 0.5 MPa)
Resistance to water	Category 2 (≥ 0.5 MPa)
Resistance to alkalinity	Category 2 (≥ 0.5 MPa)
Reparability	Repairable
Thickness	Overall thickness of the system: 0.62 mm
Applicability	Applicable
Sustainable use of natural resources	NPD
The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:	
Name Thomas Heldgaard	Date 2023-10-02
Signature Ihomas Hildzaad	Place Nr. Åby