Declaration of performance

Nr. 5002 – v2

Unique identification code of the product-type	LIP VS 30 Watertight covering kit		
Intended use	Liquid applied watertight covering kit for wet room floors and walls.		
Manufacturer	LIP Bygningsartikler A/S, Industrivej 16, 5580 Nr. Åby, Danmark		
System of AVCP	2+		
European Assessment Document	Guideline for European Technical Approval (ETAG) No. 022 Watertight covering kits for wet room floor and/or walls, Part 1 Liquid applied coverings with or without wearing surface, edition April 2007, used as European Assessment Document (EAD).		
European Technical Assessment	ETA-12/0025 of 2023-09-11		
Technical Assessment Body	ETA-Danmark A/S		
Notified body	1073		

Declared performance	
Reaction to fire	NPD
Release of corrosive substances	No dangerous materials
Vapour permeability	RH 100 → 75 %: Z_p = 220.1 GPa · s · m ² /kg and equivalent s _d = 43.0 m RH 93 → 50 %: Z_p = 223.6 GPa · s · m ² /kg and equivalent s _d = 43.7 m
Water tightness	Pass
Crack bridging ability	Category 2
Bond strength	Category 2 (≥ 0.5 MPa) for concrete substrate Category 1 (≥ 0.3 MPa) for other materials as described in clause 2 in ETA-12/0025
Scratching resistance	NPD
Joint bridging ability	Category 2
Water tightness around penetrations	Category 2
Resistance to temperature	Category 2 (≥ 0.5 MPa)
Resistance to water	Category 2 (≥ 0.5 MPa)
Resistance to alkalinity	Category 2 (≥ 0.5 MPa)
Reparability	NPD
Thickness	Minimum thickness of the membrane: 0.58 mm
Applicability	Applicable
Sustainable use of natural resources	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

-			
Name	Thomas Heldgaard	Date	2023-10-02
Signature	Thomas Hildgoord	Place	Nr. Åby
	0		